

F110.280.42

max tension 280 kN (2 x 140 kN)



Hydraulic tensioner fit to string 1, 2, 3 or 4 (up to 6 on demand) conductors.

Two hydraulic circuits allow to tension at constant force even varying the speed of stringing. The two circuits can be used independently or simultaneously, with automatic forces partition.

Equipped with engine for pull-back performances. In pull-back mode, two hydraulic circuit allow to vary the speed in both directions, allowing to use one of the hydraulic circuits or both of them matched.

FEATURES		ENGINE		TENSION PERFORMANCES	
Capstans	4 x Ø 1800 mm	Feeding	diesel	Max tension force	280 kN = 2 x 140 kN
Max conductor diameter	4 x 54 mm	Power	156 hp / 115 kW	Max speed at max tension force	3 km/h
Dimensions LxWxH	5,40x2,45x3,00 m	Cooling	water	Max speed	5 km/h
Weight	14500 kg	Electric plant	24 V		

PULL-BACK PERFORMANCES	
Max pull	280 kN = 2 x 140 kN
Max speed	1 km/h 1 km/h*

CONFIGURATION

- Two pairs of steel capstans lined with multi-grooved nylon sectors, fit for 4 conductors totally
- Machine control panel equipped with built-in electronic instrument DEG 4.0 featuring a 7" large graphic colour display and a USB port
- **Maintenance-free load cell reading system**
- **Electronic instrument by-pass**
- **Self-recovery device for sagging operations**
- Two safety negative hydraulic brakes
- Front and back conductor-drivers with nylon rollers, for 4 cond.
- Chassis with two rigid axles (tandem), tires and drawbar for towing at low speed in job-site
- Hydraulic front plough
- Attachments for anchoring and for lifting
- Heat exchanger to cool the oil in the hydraulic circuit
- Devices for coupling the two of pairs of capstans
- Three auxiliary hydraulic circuits for controlling up to 6 reel-stands (not independent)
- Grounding connection point

* According to the EC directive 97/68/CE with subsequent amendments and additions.

Performances of the machine without optional devices, at sea level and temperature 20°C. Dimensions and weights are without optional devices. All data may change without notice. Images and drawings are indicative only.

OPTIONAL DEVICES

- 005.1 Chassis with 2 damped axles (tandem), air braking system and lights
- 006.4 Arrangement of the chassis for circulation on road (homologation excluded)
- 012 Predisposition of one hydraulic circuit to feed a press for high pressure joints (max. 700 bar)
- 020.3 Set of nylon sectors with grooves fit for 6 conductors Ømax 36 mm
- 028.7 Device to start the diesel engine at low temperatures (up to -30°C)
- 037 Remote control by cable, with 10 m of cable
- 038 Radio-control (max distance 100 m)
- 045.2 Automatic clamp for 6 conductors
- 069.5 Printer for the electronic recorder, with accessories