CUTTERS

C15



Hand operated hydraulic cutters fit for cutting copper, aluminum, aldrey, steel and steel-aluminum ropes and conductors.

- Two speeds action: high speed to quickly approach the blade to the conductor and low speed for cutting
- Blades made of high strength special steel
- Openable head, with quick locking device, to cut running cables
- The head can rotate 180° to let the operator work in the most comfortable position
- Safety valve that automatically bypasses oil when reaching the max pressure
- Release device that can be operated at any stage of the operation
- C15.40.1.L pair of spare blades
- C15.50.1.L pair of spare baldes

C15.25		C15.40.1		C15.50.1		
Material	Max cutting diameter mm	Material	Max cutting diameter mm	Material	Ma	x cutting diameter mm
aluminium-steel	25	aluminium-steel	40	aluminium-steel		54
aluminium	25	aluminium	40	aluminium		54
copper	25	copper	40	copper		54
steel-ropes	18	steel-ropes	19	steel-ropes		20
Length	Weight	Length	Weight	Length	Weight	Cutting force
382	3,2	683	6,8	631	10,3	124,5 kN

C12 / C13



Ratchet cutters fit for conductors, cables and shield wires. The chain ratchet allows to cut the wire progressively with minimum effort. Insulated handles tested at 20.000 V.

C12 Cutter for ACSR and ACAR conductors. Cutting capacity up to Ø 31 mm. Length 750 mm. C12.L pair of spare blades

C13 Cutter for electric and telephonic cables. Cutting capacity up to Ø 31 mm Not fit for ACSC conductors. Length 700 mm. C13.L pair of spare blades

C13.1 Cutter for shield wires. Cutting capacity up to Ø 11 mm. Length 720 mm. C13.1.L pair of spare blades



