

CID CIS CIE



Hydraulic power pack for feeding the hydraulic presses.

- Base and protection frame
- Metallic box with handles for transport
- 2-stage pump for a faster return of the press cylinder
- Quick couplings for connecting the flexible hoses
- Exhaust valve

OPTIONAL DEVICES

- 01 Control valve for presses mounted on power unit instead of the press
- 02 Single phase electric motor 220 V (for model CIE.01)
- 03 Oil tank with capacity 25 lt (only for model CIS.01 and CID.01)
- 04 Increased capacity of the pump at 8 - 2 liters/minute
- 05 Base frame with wheels and handles for towing and lifting

	Engine	Power	Max pressure	Max flow	Tank capacity	Dimensions L x W x H	Weight
		kW	bar	l/min	l	mm	kg
CIS.01	gasoline	3,5	700	4,7 - 1,8	10	530 x 340 x 370	51
CID.01	diesel	5	700	4,7 - 1,8	10	550 x 400 x 450	60
CIE.01	three phase Electric 380V	2,2	700	2,7 - 0,8	10	530 x 340 x 370	46

PL



Hand pump for presses.

- 2-stage pump for a faster return of the press cylinder
- Light-alloy construction
- Quick couplings for connecting the flexible hoses

	Max pressure	Displacement		Tank capacity	Dimensions l x w x h	Weight
	bar	1st stage cm ³	2nd stage cm ³	l	mm	kg
PL.262	700	13	3	2,5	565 x 125 x 170	8

TF



Kit of flexible hoses with quick couplings.
Lengths: 3, 6, 10, 15, 20, 30, 40, 50, 60 m
(specify the length needed).

GR



Quick couplings for connecting two flexible hoses.