



C108.A

Galvanised steel cable roller.



FEATURES

MAX LOAD	180 kg
MAX CABLE	Ø 120 mm
ROLLER	Ø 70/110 x 185 mm
DIMENSIONS	300 x 240 x 250 mm
WEIGHT	4,1 kg

C108.A1

Heavy version with shielded bearings.



FEATURES

MAX LOAD	400 kg
MAX CABLE	Ø 200 mm
ROLLER	Ø 80/130 x 280 mm
DIMENSIONS	300 x 300 x 260 mm
WEIGHT	7,1 kg

C108.B

Aluminium cable roller with galvanised steel base.



FEATURES

MAX LOAD	200 kg
MAX CABLE	Ø 120 mm
ROLLER	Ø 75/115 x 175 mm
DIMENSIONS	300 x 240 x 250 mm
WEIGHT	4,5 kg

C108.C

Straight cable roller with 3 aluminium rollers.



FEATURES

MAX LOAD	200 kg
MAX CABLE	Ø 150 mm
ROLLER	Ø 50/60 x 100 mm
DIMENSIONS	250 x 250 x 250 mm
WEIGHT	4,9 kg

C108.E

Galvanised horizontal cable roller.



FEATURES

MAX LOAD	400 kg
MAX CABLE	Ø 120 mm
ROLLER	Ø 75/110 x 800 mm
DIMENSIONS	850 x 250 x 250 mm
WEIGHT	13 kg

C108.E1

Heavy version shielded bearings.



FEATURES

MAX LOAD	1000 kg
ROLLER	Ø 80 x 950 mm
DIMENSIONS	1000 x 250 x 250 mm
WEIGHT	22 kg

C108.F

Galvanised cable guiding run-off frame.



FEATURES

MAX LOAD	300 kg
ROLLER	Ø 35 x 620 mm
DIMENSIONS	1050 x 470 x 520 mm
WEIGHT	14 kg

C108.F1

Heavy version with shielded bearings.



FEATURES

MAX LOAD	1000 kg
ROLLER	Ø 80 x 700 mm
DIMENSIONS	1200 x 600 x 450 mm
WEIGHT	28 kg

Performances of the machine without optional devices, at sea level and temperature 20°C. Dimensions and weights are without optional devices. All data may change without notice. Images and drawings are indicative only.