



C109.G

C109.G Tren de rodillos de arqueta, de acero galvanizado.

C109.G1 Versión con rodillos de aluminio.



	RODILLOS	DIMENSIONES	PESO
	mm	mm	kg
C109.G	Ø75/110x180	500x220x400	13
C109.G1	Ø70/130x170	500x220x400	17

C109.H

Barra telescópica con rodillo de aluminio de guía del cable.



	RODILLOS	LONGITUD BARRA	PESO
	mm	mm	kg
C109.H.1	Ø110/210x110	300-500	9,5
C109.H.2	Ø110/210x110	500-800	10
C109.H.3	Ø110/210x110	600-1000	13
C109.H.4	Ø110/210x110	1000-1500	16
C109.H.5	Ø110/210x110	1500-1800	18
C109.H.6	Ø110/210x110	1800-2400	23

C109.I


Doble barra telescópica con rodillo central de guía del cable.



	RODILLOS	LONGITUD BARRA	PESO
	mm	mm	kg
C109.I.1	Ø110/210x110	300-500	12
C109.I.2	Ø110/210x110	500-800	15
C109.I.3	Ø110/210x110	600-1000	19
C109.I.4	Ø110/210x110	1000-1500	24
C109.I.5	Ø110/210x110	1500-1800	27
C109.I.6	Ø110/210x110	1800-2400	30

C109.L

Dispositivo de guía del cable con 4 rodillos de protección.





	PASAJE ENTRE RODILLOS	RODILLOS	DIMENSIONES	PESO
	mm	mm	mm	kg
C109.L	250	Ø 60	550x130x500	15

C109.M

C109.M Dispositivo de guía del cable con 4 rodillos de protección

C109.MA Barra telescópica para guía C109.M

C109.MB Dispositivo de guía del cable con 4 rodillos de protección Ø 60 mm (C109.M), completo de barra telescópica (C09.MA)



	PASAJE ENTRE RODILLOS	RODILLOS	DIMENSIONES	PESO
	mm	mm	mm	kg
C109.M	250	Ø 60	550x130x500	15

	LONGITUD BARRA	PESO		LONGITUD BARRA	PESO
	mm	kg		mm	kg
C109.MA.1	500-800	7	C109.MB.1	500-800	10
C109.MA.2	600-1000	10	C109.MB.2	600-1000	13
C109.MA.3	1000-1700	12	C109.MB.3	1000-1700	15
C109.MA.4	1400-2400	14	C109.MB.4	1400-2400	17