



# F306.18.CC

Hydraulic power unit with one hydraulic circuit (closed type) fit to feed reel-stands drive.



## ENGINE

FEEDING	gasoline
POWER	18 hp / 13,2 kW
REVOLUTIONS PER MINUTE	air
COOLING SYSTEM	12 V
STARTING	1,20x0,90x0,95 m
DIMENSIONS LXWXH	475 kg
WEIGHT	68 kg

## PERFORMANCES

FIT FOR MOTORIZATIONS OF REEL-STANDS WITH CAPACITY	120-500 kN
PUMP DELIVERY (VARIABLE)	0-28 cm <sup>3</sup>
WORKING PRESSURE	210 bar

## ALSO AVAILABLE F306.21.CC

## CONFIGURATION

- Control panel with joystick for puller use, dynamometer and preselector of max pull force, valve to adjust the tension force and control for unlocking the negative brake.
- Group of quick couplings to connect the hydraulic hoses.
- Rigid axle, tires, hand brake and drawbar for towing at low speed in the subsite.
- Metallic cover with doors.
- Oil cooling system.

## OPTIONAL DEVICES

- 011** Auxiliary hydraulic circuit for additional equipment (like hydraulic cylinders).
- 028.1** Water-cooled diesel engine (F306.18.CC only)
- 078.1** Set of flexible hoses (available lengths 7,10,15 m)