

F10.120

Trailer fit to transport and unwind reels of cable weighing up to 10000 kg.



FEATURES

DIMENSIONS	7,30x3,50x2,70 m
TOTAL WEIGHT WITH DRUM	12000 kg
DRUM MAX DIAMETER	3000 mm
DRUM MAX WIDTH	1600 mm
PERFORMANCES WITH OPTIONAL DRIVE (OPT.408.4 or 408.5)	
PULLING FORCE	0 - 9 kN
PULLING SPEED	0 - 60 m/min

ALSO AVAILBLE TRAILERS WITH DIFFERENT CAPACITY

CONFIGURATION

- Framework made of 3 steel sections.
- Spindle rotating on ball joints, with arm for close and drag the reel, and collars for wooden reel.
- Safe mechanical locking in working position.
- Mechanical locking of the spindle rotation for safe transport.
- Single rigid axle and rigid towing assembly.
- Towing speed 40 Km/h.
- Front support.
- No brakes and No lights.

OPTIONAL DEVICES

006.1 12V lig	ght system.
----------------------	-------------

006.6 Hand parking brake for trailer.

425 Mechanical back supports.

438 Hydraulic reel lift with hand pump.

005.1 Damped tandem axle, towing speed 60 km/h. Complete with ABS system.

005.3 Damped tandem axle, towing speed 80 km/h. Complete with ABS system and Pneumatic suspensions.

029.2 Electric start of the diesel/gasoline engine, with battery.

401 Devices fit for using steel reels with the reel-elevator.

408.4 Hydraulic drive with quick connections for controlling the reel rotation both recovering and releasing cables, complete with power unit and gasoline engine.

408.5 Hydraulic drive with quick connections for controlling the reel rotation both recovering and releasing cables, complete with power unit and diesel engine.

410.1 Disk brake with manual regulation of the braking to keep under control the unwinding.

THE LINK LLIKE ON

OMAC I TALY