



21.12

Anti-twisting galvanised steel rope specifically designed for stringing operations. Made up of 12 braided strands. High resistant to break, antitwisting, flexible, safe and easy to handle. The linear contact between the braided strands grants a low stress on the rope. Supplied wound up on steel or wooden reels.



	Nominal diameter	Breaking load	Weight	Standard Lengths (*)	
	mm	kN	kg	m	
21.12.08	8	44	0,22	1000	on steel reel Ø 1100 mm Mod. F162.110
21.12.10	10	72	0,35	1000	
21.12.13	13	105	0,55	1000	
21.12.16	16	163	0,80	1000	
21.12.18	18	235	1,07	800	on steel reel Ø 1400 mm Mod. F162.140
21.12.20	20	268	1,24	1000	
21.12.22	22	330	1,56	900	
21.12.24	24	380	1,80	800	
21.12.28	28	480	2,80	500	

(*) other lengths on request

HIGH RESISTANCE (18 strands)

	Nominal diameter	Breaking load	Weight	Standard Lengths (*)	
	mm	kN	kg	m	
21.18.22	22	402	1,86	900	on steel reel Ø 1400 mm Mod. F162.140
21.18.24	24	490	2,34	800	
21.18.30	30	720	3,25	400	

(*) other lengths on request

OPTIONAL DEVICES

- 146.2 Spliced eyes at both ends
- 146.3 Clamped eyes at both ends