

CID CIS CIE



Hydraulic power pack for feeding the hydraulic presses.

- Base and protection frame.
- Metallic box with handles for transport.
- 2-stage pump for a faster return of the press cylinder (except model CIS.02 single-stage).
- Quick couplings for connecting the flexible hoses.
- Exhaust valve.
- CIS.02 model equipped with heat exchanger for cooling the hydraulic oil.

OPTIONAL DEVICES

- 01 Control valve for presses mounted on power unit instead of the press.
- 02 Single phase electric motor 220 V (for model CIE.01).
- 03 Oil tank with capacity 25 lt (only for model CIS.01 and CID.01).
- 04 Increased capacity of the pump at 8 - 2 liters/minute.
- 05 Base frame with wheels and handles for towing and lifting.

	Engine	Power	Max pressure	Max flow	Tank capacity	Dimensions L x W x H	Weight
		kW	bar	l/min	l	mm	kg
CIS.01	gasoline	3,5	700	4,7 - 1,8	10	530 x 340 x 370	51
CIS.02	gasoline	3,5	700	3	10	520 x 400 x 400	42
CID.01	diesel	5	700	4,7 - 1,8	10	550 x 400 x 450	60
CIE.01	three phase Electric 380V	2,2	700	2,7 - 0,8	10	530 x 340 x 370	46

PL



Hand pump for presses.

- 2-stage pump for a faster return of the press cylinder.
- Light-alloy construction.
- Quick couplings for connecting the flexible hoses.

	Max pressure	Displacement		Tank capacity	Dimensions l x w x h	Weight
	bar	1st stage	2nd stage	l	mm	kg
		cm ³	cm ³			
PL.262	700	13	3	2,5	565 x 125 x 170	8

TF



Kit of flexible hoses with quick couplings.
Lengths: 3, 6, 10, 15, 20, 30, 40, 50, 60 m
(specify the length needed).

GR



Quick couplings for connecting two flexible hoses.

Dimensions and weights are without optional devices. All data may change without notice. Images and drawings are indicative only.