CABLE REMOTE CONTROL



037

Remote control by cable. Fit for "puller" and "puller-tensioner" machines with 1, 2, 3 or 4 hydraulic circuits.

The control is complete with:

- Minijoystick for controlling the rotation of the capstans
- Speed adjustment control
- Emergency stop button
- 10-m of the connection cable

OPTIONAL DEVICES

- O1 Dynamometer to read the pulling force, metercounter and speedometer.
- 02 Engine start/stop.
- 03 Engine accelerator.
- 04 Tension force adjustment control (tensioner).

RADIO REMOTE CONTROL



038.1

Radio remote control fit for "puller" machines.

Max operational distance: up to 100 m.

The radio-control is complete with:

- Two buttons for controlling the capstans rotation
- Speed-adjustment control
- Emergency stop button
- Back-up cable for connect radio control to the machine in case of radio-failure
- Dynamometer to read the pulling force, metercounter and speedometer.

(Only for the following machine models: F275.30 and F280.35)



038

Radio remote control. Fit for "puller" and "puller-tensioner" machines with 1,2,3 or 4 hydraulic circuits.

Max operational distance: up to 100 m.

The radio-control is complete with:

- Minijoystick for controlling the capstans rotation
- Speed adjustment control (puller)
- Emergency stop button
- Back-up cable to connect the radio remote control to the machine in case of radio-failure

OPTIONAL DEVICES

- O1 Dynamometer to read the pulling force, metercounter and speedometer.
- 02 Engine start/stop.
- 03 Engine accelerator.
- 04 Tension force adjustment control (tensioner).

Dimensions and weights are without optional devices. All data may change without notice. Images and drawings are indicative only.

