F10.50

Trailer fit to transport and unwind reels of cable weighing up to 4000 kg.

FEATURES

DIMENSIONS	6,40x2,50x2,60 m
TOTAL WEIGHT WITH DRUM	5000 kg
DRUM MAX DIAMETER	3000 mm
DRUM MAX WIDTH	1400 mm
PERFORMANCES WITH OPTIONAL DRIVE (OPT.408.4 or 408.5)	
PULLING FORCE	0 - 9 kN
PULLING SPEED	0 - 60 m/min

ALSO AVAILABLE TRAILERS WITH DIFFERENT CAPACITY

CONFIGURATION

- Spindle rotating on ball joints, with arm for close and drag the reel, and collars for wooden reel
- Safe mechanical locking in working position
- Mechanical locking of the spindle rotation for safe transport
- Hydraulic reel lift with hand pump
- Single rigid axle and rigid towing assembly
- Towing speed 40 Km/h
- 12V light system
- Hand parking brake for trailer
- Front support

OPTIONAL DEVICES

425	Mechanical back supports
007-A	Damped single axle, towing speed 60 km/h. Complete with ABS system
007-B	Damped single axle, towing speed 80 km/h.Complete with ABS system and pneumatic suspensions
018.11	Framework made of 3 steel sections
029.2	Electric start of the diesel/gasoline engine, with battery
408.4	Hydraulic drive with quick connections for controlling the reel rotation both recovering and releasing cables, complete with power unit and gasoline engine
408.5	Hydraulic drive with quick connections for controlling the reel rotation both recovering and releasing cables, complete with power unit and diesel engine
410.1	Disk brake with manual regulation of the braking to keep under control the unwinding

Performances of the machine without optional devices, at sea level and temperature 20°C.
Dimensions and weights are without optional devices. All data may change without notice. Images and drawings are indicative only.