MAST 131.1.X - 131.5.X

Mast for the installation of contact wires, with an extension for installing the catenary wire to help reach the desired height during setup. Available in different heights.

MAST DIMENSIONS

	HEIGHT*
131.1.X	4900 - 5300 - 6000 - 7000 mm
131.5.X	1200 - 1500 - 1800 mm

* From the height of our platform/machine

CONFIGURATION

- Tilting range from ± 400 mm to ± 2000 mm
- Main structure made of galvanized steel complete with base-frame for the attachments for the mast
- Mast equipped with sensors to ensure the correct tilting and the correct deployment of the mast during the transport to increase safety onsite
- The Mast can be supplied as a stand-alone machine complete with its own electrical panel, hydraulic system, control valves, and base frame
- Mast equipped with nylon rollers to ensure smooth sliding of the cable/contact wire

OPTIONAL DEVICES

QE	Electric power supply (12 or 24 Vdc), supplied by the customer. (please confirm 12 or 24 Vdc)
MO	Electro-Hydraulic control valve complete with hoses. Feeding Pump and Electric Control Unit - Not included
131.4	Base frame for MAST Dimensions to be specify . Max Width 2000/2300 mm Max Length 1300/1500 mm
093.2	Protective barriers
038.9.A.1	Radio remote control for telescopic mast operations with 10 meters back up cable
037	Remote control by cable, with 10 m of cable

Performances of the machine without optional devices, at sea level and temperature 20°C.
Dimensions and weights are without optional devices. All data may change without notice. Images and drawings are indicative only.